









| 172 1 EA VG4Ø | BRAISING PAN |
|------------------------------|--------------|
| CW 0.50 16 AFF | |
| <pre> 120(1) 9.0A </pre> | 5-15 |
| | 16 AFF |
| | _ |
| 175 1 EA V4B36S | RANGE |
| ♠ 19Ø MBTU 1.25 | 32 AFF |
| | |

GENERAL NOTES - PLEASE READ

VENTILATION: ALL COOKING EQUIPMENT MUST BE VENTILATED BY AN APPROVED APPLIANCE IN ACCORDANCE WITH ALL APPLICABLE CODES.

FIRE SUPPRIESSION: ALL COOKING EQUIPMENT MUST BE PROTECTED BY AN APPROVED FIRE SUPPRESSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.

CONNECTIONS:
ALL PIPING, FITTINGS, AND INTERCONNECTION SERVICES SHOWN ARE TO BE SUPPLIED AND INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES.

GAS CONNECTIONS:

GAS CONNECTIONS:
EXTERNAL GAS REGULATORS, FLEXIBLE GAS LINES AND RESTRAINING CABLES PROVIDED
WITH THE EQUIPMENT MUST BE INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE
WITH ALL LOCAL CODES. INCOMING GAS MANIFOLD SUPPLY PRESSURE MUST
NOT EXCEED 0.5 PSI (14" W.C.)

BY OTHERS: VERIFY ALL EQUIPMENT LISTED AS BY OTHERS FOR SIZE AND MECHANICAL SERVICE REQUIREMENTS.

NOTE: IN LINE WITH THE POLICY TO CONTINUALLY IMPROVE ITS PRODUCTS, THE MANUFACTURES RESERVE THE RIGHT TO CHANGE MATERIALS AND SPECIFICATIONS WITHOUT NOTICE.

01-20-2022 01-20-2022 : 11:38:26a

| . | CONNECTION | POIN |
|----------|------------|------|
| | COLD VATED | |

(C) COLD WATER

(H) HOT WATER

(HC) HOT + COLD
WATER

D DRAIN

POWER

SWITCH
CORD SET
C CONV OUTLET RECP
DUPLEX RECPTACLE
SINGLE RECPTACLE

GR STEAM RETURN

CR STEAM RETURN
ST STEAM TAKE OFF
VE EXHAUST VENT
VS SUPPLY VENT

RF REFRIGERATION

PROJECT CODE MAVB3

VULCAN HART COMPANY

AS NOTED

DATE: DATE

DRAWN BY: DDB

VH-VAVB3

NEXT STEP 913 WEST S ANNAPOLIS,

DESIGN

or 1