













FRTTOP-36CMD V4B36S 36"	FRTTOP-36CMD VCBB36B 36"	VICM48 ARS48 VCCG48-IR 48"	FRTTOP-36CMD ARS36 4" FEET V4B36 36"
GAS HA CR C LH	CRC LH		122 / 125 H H UND H UND H UND H UND H UND H UND UND H UND UND UND UND UND UND UND UND

107 1 EA V4B36S	RANGE
♠ 190 MBTU 1.25	32 AFF
108 1 EA VCBB36	CHRABROILER
Ø 99 MBTU 1.25	32 AFF
1Ø9 1 EA VCCGR48	GRIDDLE
(1) 120 (1) 2.0A	5-15
96 MBTU Ø.75	34 AFF
11Ø 1 EA ARS48	REFRIGERATED BASE
3 120(1) 6.7A	5-15
111 1 EA VICM48	CHEESE MELTER WALL MOUNT
♠ 4Ø MBTU Ø.75	78 AFF
122 1 EA ARS36	REFRIGERATED BASE
3 120(1) 6.7A	5-15
-	
125 1 EA V4B36	RANGE
↑ 14Ø MBTU 1.25	32 AFF

## GENERAL NOTES - PLEASE READ

ALL COOKING EQUIPMENT MUST BE VENTILATED BY AN APPROVED APPLIANCE IN ACCORDANCE WITH ALL APPLICABLE CODES.

ALL COOKING EQUIPMENT MUST BE PROTECTED BY AN APPROVED FIRE SUPPRESSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE CODES.

CONNECTIONS: ALL PIPING, FITTINGS, AND INTERCONNECTION SERVICES SHOWN ARE TO BE SUPPLIED AND INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES.

GAS CONNECTIONS:
EXTERNAL GAS REGULATORS, FLEXIBLE GAS LINES AND RESTRAINING CABLES PROVIDED WITH THE EQUIPMENT MUST BE INSTALLED BY LICENSED CONTRACTORS IN ACCORDANCE WITH ALL LOCAL CODES. INCOMING GAS MANIFOLD SUPPLY PRESSURE MUST NOT EXCEED 0.5 PSI (14" W.C.)

BY OTHERS: VERIFY ALL EQUIPMENT LISTED AS BY OTHERS FOR SIZE AND MECHANICAL SERVICE REQUIREMENTS.

IN LINE WITH THE POLICY TO CONTINUALLY IMPROVE ITS PRODUCTS, THE MANUFACTURES RESERVE THE RIGHT TO CHANGE MATERIALS AND SPECIFICATIONS WITHOUT NOTICE.

D DRAIN POWER \$ SWITCH CORD SET © CONV OUTLET RECP DUPLEX RECPTACLE

CONNECTION POINT

C COLD WATER (H) HOT WATER

HOT + COLD WATER

SINGLE RECPTACLE (SS) STEAM SUPPLY CR STEAM RETURN

ST STEAM TAKE OFF VE EXHAUST VENT VS) SUPPLY VENT (RF) REFRIGERATION

10-20-2021

PROJECT CODE SUMST

DESIGN 913 WEST S ANNAPOLIS,

> AS NOTED DATE: \_\_10/20/2021 DRAWN BY: DDB

VH-SUMST